



DV-8200 / DU-8200 UV/VIS Spectrophotometer

※ Specifications:

Model	DV-8200	DU-8200
Wavelength Range	320-1100nm	190-1100nm
Spectral Bandwidth	2.0nm or 4.0nm optional	
Optical System	Single Beam, Blazed Holographic Grating (1200 lines/mm)	
Wavelength Accuracy	±0.8nm	
Wavelength Repeatability	≤0.2nm	
Wavelength Setting	Auto, Resolution 0.1nm	
Photometric Range	0~200%T, -0.3~3A, 0~9999C	
Photometric Accuracy	±0.002A (0~0.5A), ±0.004A (0.5~1A), ±0.3%T (0~100%T)	
Photometric Repeatability	≤0.001A (0~0.5A), ≤0.002A (0.5~1A), ≤0.2%T (0~100%T)	
Stray Light	≤0.1%T(220/360nm)	
Scan Speed	High, Medium, Low. Max.1000nm/minute	
Baseline Flatness	±0.003A±	
Stability	0.002A/h (500nm,0A)	
Noise	≤0.2%T/3min(250/500nm,0%T);≤0.5%T/3min(250/500nm,100%T)	
Sample Compartment	Accommodate 5-100mm Pathlength Cuvette	
Detector	Silicon Photodiode	
Lamps	Tungsten Lamp & Deuterium Lamp (Pre-aligned)	
Display	Graphic LCD (128x64 Dots)	
Keypad	11-key Membrane Keypad	
Output Port	USB Port & RS232 Port	
Printer	Mini Serial Printer; PC Printer	
PC Software	Optional PC Scanning Software	
Power Requirements	AC 90-250V, 50/60Hz	
Dimension	431x318x195mm	
Net Weight / Gross Weight	8.2kgs / 12kgs	9kgs / 13kgs

8200 series spectrophotometer is the ideal instrument for education and QC laboratories. They are simple to fit a curve by using your standard. They are widely used in colleges and quantitative analysis lab.

※ Features

- Small fine design, space saving
- The excellent optical and electric system
- Low noise and Low stray light
- Large LCD display (128*64 Dots), can display curve
- High quality grating, detector and lamps
- Data and Curve can be stored in real-time
- Auto setting WL, auto Blank
- Easy to change Pri-aligned lamps
- Reinforced baseboard and bracket assures durability

※ Function:

- Photometric: T%, Abs
- Quantitative: Standard Curve
- System Utility
 - * WL Scan (Spectrum Scan) (PC)
 - * Time Scan (Kinetics) (PC)
 - * DNA/Protein Test (PC)
 - * Multi-WL Test (PC)

